

3) a transparent cover adhered to the lens array substrate with an adhesive that covers said microlens and said step portion.

4. (Amended) A method for fabricating an electro-optical device which comprises a pair of substrates including a first substrate and a second substrate, a liquid crystal enclosed between the pair of substrates, and a plurality of pixels formed in a matrix disposed within said pair of substrates, said first substrate including a lens array substrate, said method comprising:

forming a plurality of convex microlenses with one microlens corresponding to each of said plurality of pixels on said lens array substrate;

forming a step portion substantially equal in height to said microlenses throughout a periphery of said first substrates;

adhering a transparent cover to said lens array substrate with an adhesive to cover said microlenses and said step portion;

forming a sealing material;

superposing the first substrate on the second substrate to face said step portion with the sealing material therebetween, the periphery of the first substrate completely overlapping the sealing material; and

curing said sealing material while pressing said first substrate on the second substrate.

7. (Amended) A method for fabricating an electro-optical device which comprises a pair of substrates including a first substrate and a second substrate, an electro-optical material enclosed between the pair of substrates, and a plurality of pixels formed in a matrix disposed within said pair of substrates, said first substrate including a lens array substrate, said method comprising:

forming a plurality of convex microlenses with one microlens corresponding to each of said plurality of pixels on said lens array substrate;

Sub 03 cont.
Part.

forming a step portion substantially equal in height to said microlenses throughout a periphery of said lens array substrate;

bonding a transparent cover to said lens array substrate with an adhesive so as to cover said microlenses and said step portion;

forming a sealing material;

superposing the first substrate on the second substrate to face said step portion with said sealing material therebetween, the periphery of the first substrate completely overlapping the sealing material; and

curing said sealing material while applying pressure from an exterior of said pair of substrates.

10. (Amended) An electro-optical device comprising:

Sub 04

a pair of substrates including a first substrate and a second substrate adhered together with a sealing material; and

an electro-optical material enclosed between said pair of substrates, said second substrate having a plurality of scanning lines, a plurality of data lines intersecting said plurality of scanning lines, a pixel having a switching device connected to each of said scanning lines and each of said data lines, and a pixel electrode connected to said switching device, and the first substrate including:

- 1) a lens array substrate provided with a plurality of convex microlenses with one microlens formed corresponding to each of said pixel,
- 2) a step portion being substantially equal height to said microlenses throughout a region completely overlapping said sealing material, and

Sub
P4 Cont
C1

3) a transparent cover adhered to the lens array substrate with an adhesive that covers said microlenses and said step portion.

Sub
P5
C1

12. (Twice Amended) An electro-optical device, comprising:
a pair of substrates including a first and a second substrate adhered together with a sealing material;
an electro-optical material enclosed between said pair of substrates; and
a plurality of pixels formed in a matrix disposed within said pair of substrates, said first substrate including:
1) a lens array substrate provided with a plurality of convex microlenses with one microlens corresponding to each of said plurality of pixels, the plurality of microlenses being provided at one side of the first substrate,
2) a step portion formed on the one side of the first substrate throughout a region completely overlapping said sealing material, and
3) a transparent cover adhered to the lens array substrate with an adhesive that covers said microlenses and said step portion.

Sub
P5
C1

13. (Amended) A method for fabricating an electro-optical device which comprises a pair of substrates including a first substrate and a second substrate, a liquid crystal enclosed between the pair of substrates, and a plurality of pixels formed in a matrix disposed within said pair of substrates, said first substrate including a lens array substrate, said method comprising:
forming a plurality of convex microlenses with one microlens corresponding to each of said plurality of pixels on said lens array substrate, the plurality of microlenses being formed at one side of the first substrate;
forming a step portion on the one side of the first substrate throughout a periphery of said first substrate;

adhering a transparent cover to said lens array substrate with an adhesive to
 cover said microlenses and said step portion;
 forming a sealing material;
 superposing the first substrate on the second substrate to face said step portion
 with the sealing material therebetween, the periphery of the first substrate completely
 overlapping the sealing material; and
 curing said sealing material while pressing said first substrate on the second
 substrate.

14. (Amended) A method for fabricating an electro-optical device which
 comprises a pair of substrates including a first substrate and a second substrate, an electro-
 optical material enclosed between the pair of substrates, and a plurality of pixels formed in a
 matrix disposed within said pair of substrates, said first substrate including a lens array
 substrate, said method comprising:

forming a plurality of convex microlenses with one microlens corresponding
 to each of said plurality of pixels on said lens array substrate, the plurality of microlenses
 being formed on one side of the first substrate;

forming a step portion on the one side of the first substrate throughout a
 periphery of said first substrate;

bonding a transparent cover to said lens array substrate with an adhesive so as
 to cover said microlenses and said step portion;

forming a sealing material;

superposing the first substrate on the second substrate to face said step portion
 with the sealing material therebetween, the periphery of the first substrate completely
 overlapping the sealing material; and

curing said sealing material while applying pressure from an exterior of said
 pair of substrates.

15. (Twice Amended) An electro-optical device, comprising:

a pair of substrates including a first and a second substrate adhered together with a sealing material;

an electro-optical material enclosed between said pair of substrates, said second substrate having a plurality of scanning lines, a plurality of data lines intersecting said plurality of scanning lines, a pixel having a switching device connected to each of said scanning lines and each of said data lines, and a pixel electrode connected to said switching device, and the first substrate including:

- 1) a lens array substrate provided with a plurality of convex microlenses with one microlens corresponding to each of said plurality of pixels, the plurality of microlenses being formed on one side of the first substrate,
- 2) a step portion formed on the one side of the first substrate throughout a region completely overlapping said sealing material, and
- 3) a transparent cover adhered to the lens array substrate with an adhesive that covers said microlenses and said step portion.

16. (Amended) An electro-optical device, comprising:

a first substrate;

a second substrate;

a sealing material that adheres the first and second substrates together;

an electro-optical material disposed between the first and second substrates;

and

a plurality of pixels arranged in a matrix and disposed between the first and second substrates;

the first substrate including:

a lens array substrate that defines a plurality of convex microlenses,

a step portion formed on the one side of the first substrate in a region
 overlapping the sealing material, the step portion being substantially equal in height to the
 microlenses, a width of the step portion being wider than a width of the sealing material,
 a transparent cover, and
 an adhesive that adheres the transparent cover to the lens array
 substrate.

24. (Amended) A method of manufacturing an electro-optical device that includes
 a first substrate having a lens array substrate and a transparent cover, a second substrate, an
 electro-optical material disposed between the first and second substrates, sealing material,
 and a plurality of pixels arranged in a matrix disposed between the first and second
 substrates, the method comprising:
 forming a plurality of microlenses on the lens array substrate;
 forming a step portion on the one side of the first substrate on a peripheral of
 the first substrate, the step portion being substantially equal in height to the microlenses;
 adhering the transparent cover to the lens array substrate;
 superposing the first substrate over the second substrate to face the step
 portion with the sealing material therebetween; and
 curing the sealing material while pressing the first substrate toward the second
 substrate so that a width of the step portion is wider than a width of the sealing material.

REMARKS

Claims 1-5, 7, 8 and 10-26 are pending. By this Amendment, claims 1, 4, 7, 10, 12-
 16 and 24 are amended.

The attached Appendix includes marked-up copies of each rewritten claim (37 C.F.R.
 §1.121(c)(1)(ii)).

Reconsideration based on the following remarks is respectfully requested.